Typical Exterior Wall (Stucco)

TYPICAL EXTERIOR WALL WITH STUCCO

TWS-A001 *COLOR FOR VISUAL CLARIFICATION ONLY*

MINIMUM REQUIREMENTS

1. THERMAX INSULATION SHIP-LAPPED HORIZONTAL EDGE (ON 1.5" AND GREATER THICKNESSES) SHOULD BE LAYERED IN A SHINGLE-LAP FASHION (AS SHOWN) TO PROMOTE WATER SHEDDING AND PREVENT MOISTURE INTRUSION AT HORIZONTAL INSULATION JUNCTURES.
2. APPLY DIAMOND MESH LATH WITH LONG DIMENSIONS PERPENDICULAR TO STUD FRAMING AND ATTACH WITH GALVANIZED STEEL SCREWS OF TYPE & LENGTH SUITABLE FOR MIN. 2/3" PENETRATION OF STEEL STUD SYSTEM.
3. MIN. ADHESION OF LIQDUIDARMOR OR WEATHERMATE FLASHING ONTO EACH FACE OF THERMAX BASED ON DETAIL TWS-G005.

Dow Building Solutions | 1501 Larkin Center Drive, 200 Larkin, Midland, MI 48674 | 1-866-583-2583 | November 2016: Reference most recent set at dowbuildingsolutions.com
®™TRADEMARK OF THE DOW CHEMICAL COMPANY (*DOW*) OR AFFILIATE. REFERENCE DETAIL FOR PLANNING PURPOSES ONLY. REGISTERED PROFESSIONAL TO REVIEW. MAY NOT BE USED FOR CONSTRUCTION.